

Item No. 8900KA015

pascom multitouch cash register

With unique touch technology

This powerful cash register has a frameless 15-inch display and can be used for almost all applications because of its numerous mounting options, like customer monitor, smartcard reader, waiter lock, fingerprint reader and RFID reader.


Because of the unique touch technology, the cash register is extremely robust. It can even be operated with gloves. On the front the cash register is completely dustproof and waterproof.

Advantages

- Completely dustproof and waterproof Front side (IP 66)
- Frameless 15" multitouch screen
- Configurable for almost all applications
- Robust metal housing

Various options

- 7" customer monitor
- Smartcard reader
- Waiter lock
- Fingerprint reader
- RFID reader



Technical Specifications VariPos 750

Main Board	Processor	Intel® Celeron® Processor J1900 (2M Cache, up to 2.42 GHz)
	Chipset	CPU Integrated
	System Memory	1 x DDR3L SO-DIMM up to 8GB
Display & Touch	LCD Size	15" TFT LCD (LED backlight)
	Brightness	350nits
	Resolution	1024 x 768
	Touch Technology	True Flat Projected Capacitive Technology
Storage	HDD / SSD	1 x SATA (2.5") HDD or SSD
	DC Input	1 x Mini Din 4P (DC 19V only)
	Cash Drawer	1 x RJ-11 (Support DC +12V or +24V (default)) port supports 2 cash drawers
I/O & Expansion	LAN Port	1 x Gigabit Ethernet by RJ-45
	USB Port	2 x USB 2.0, 4 x USB3.0
	COM Port	3 x RS-232 (COM1/2:DB-9, COM3:RJ-48) w/ RI/5V/12V Selectable by BIOS (default is RI)
	Audio Port	N/A
	PS/2 Port	N/A
	LPT Port	N/A
	VGA Port	1 x DB-15 VGA port Power enable by BIOS setting (default disable)
	Bus Expansion	1 x Mini-PCI-E Slot
	Power Switch	1 x power on / off switch button
	Speaker	HD Audio, 2W Speaker x 2
OS Support	Win10 IoT 2016, Win8.1, Win7	
Power Adapter	External adapter, DC Model:65 Watts, Voltage:+19VDC 3.42 Amax	
Compliance	Certifications	CE, FCC, LVD, RoHS
	Protection	IP 66 on front panel
VESA Mount	100mm x 100mm VESA	
Material	Main Unit: Die-Cast Aluminum ; I/O Cover: Plastic	
Color	Main Unit: Black	
Dimension(Wx H x D)	370 x 300 x 236 mm	
Weight	7 kg	
Environmental	Operating Condition	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
	Storage Condition	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing
Optional Accessories	VFD	2 x 20 attached
	MSR	USB Type
	iButton	USB Type
	SCR	USB Type
	Finger Print	USB Type
	RFID	USB Type, 13.56 MHZ
	2nd Display	10.4" Resolution 800 x 600
Carton	L 404 x W 304 x H 505 mm	