



Item No. XS-O2Z0000005005

# O2xS Cylinder reading module IP66

Easy installation without complex wiring



The pascom O<sup>2</sup>xS Cylinder reading module is a universal, battery-operated locking unit, which is simply plugged onto the cylinder.

Depending on your needs, the reading module can be assembled as a double knob cylinder with single-sided or double-sided authorization, half-cylinder, furniture lock or padlock.



Knob cylinder with single-sided authorization



Knob cylinder with double-sided authorization



Half cylinder



Furniture lock



Padlock

The communication electronics and the mechatronics are located together with the batteries in the reading module.

Replacement of the batteries is possible in an assembled condition and only with authorization. Completely discharged batteries can be charged using the low power adapter. Disassembly is possible only with authorization.

## Technical specifications

Transponder:	Java Card/MIFARE ISO14443/13,56 MHz
Batteries:	2 pcs. CR2 Lithium 3V
Operating temperature:	+5 °C to +65 °C
Storage temperature:	-40 °C to +65 °C
Casing:	nickel-plated brass
Protection:	IP66
Mounting:	Outdoor, suitable for use in fire and smoke resistant doors according to DIN EN 1634
Prepared for pascom FSM online module LAN	

## Versions

Item-No. XS-O2Z0000005000  
Cylinder reading module (IP65) indoor

## Equipment



Item-No. XS-O2ZK000000001  
Mechanic Knob D=29,0



Item-No. XS-O2ZZ0xxxxxxxxx  
Cylinder, Lengths  
from 26/26 to 70/70 mm



Item-No. XS-O2ZZ1xxxxxxxxx  
Half cylinder, Lengths  
from 26/10 to 100/10 mm



Item-No. XS-O2MA000000000  
Furniture lock adapter